



DATE: July 1, 2010

TO: *All Prospective Proposers*

SUBJECT: *Addendum #1 – Forsyth Fountain Painting Re-bid – Bid No. 10.175*

The bid opening date remains as scheduled for **Tuesday, July 20, 2010** at 1:30 P.M. Please note the following changes to the specifications:

Change Section 4.4 to read: Quality Assurance: The Contractor shall provide documented experience of five (5) years proven satisfactory painting experience with demonstrated experience on similar structures of historic nature and shall maintain a qualified crew of painters throughout the duration of the work.

You must acknowledge receipt of the addendum. For your convenience, a revised copy of page 10 is included. We appreciate your interest in doing business with the City of Savannah and hope that you will respond to this solicitation.

Sincerely,

Margaret H. Joyner
Purchasing Director

supervision required to complete all exterior painting.

- 4.3 The work shall also include, but not necessarily be limited to surface preparation of substrates as required for acceptance of painting, including cleaning, pre-treatment, and priming as needed.

4.4 Quality Assurance: The Contractor shall provide documented experience of five (5) years proven satisfactory painting experience with demonstrated experience on similar structures of historic nature and shall maintain a qualified crew of painters throughout the duration of the work.

- 4.4.1 All materials, preparation and workmanship shall conform to accepted professional standards.

- 4.4.2 All paint manufacturers and products used shall be professional quality and labeled for outdoor use under severe conditions.

- 4.4.3 All surfaces requiring painting shall be inspected by the Park and Tree Department who shall notify the Contractor in writing of any defects or problems, prior to commencing painting work, or after the prime coat shows defects in the substrate.

4.5 Regulatory Requirements: Conform to work place safety regulations and requirements of those authorities having jurisdiction for storage, mixing, application and disposal of all paint and related hazardous materials.

4.6 Submittals:

- 4.6.1 Submit manufacturer's product data for each coating including generic description, technical data, surface preparation and application instructions.

- 4.6.2 Submit manufacturer's color samples. Color to be semi-gloss white.

- 4.6.3 At project completion provide an itemized list complete with manufacturer, paint type and color-coding for all colors used for Owner's later use in maintenance.

4.7 Product Delivery, Storage, and Handling: Deliver and store all painting materials in sealed, original labeled containers bearing manufacturer's name, brand name, type of paint or coating and color designation, standard compliance, materials content as well as mixing and/or reducing and application requirements in strict accordance with manufacturer requirements.

4.8 Environmental, Waste Management and Disposal Requirements:

- 4.8.1 Perform no painting work when the ambient air and substrate temperatures, relative humidity and dew point and substrate moisture content is below or above requirements for exterior work.

- 4.8.2 Apply paint only to dry, clean, properly cured and adequately prepared surfaces in areas where dust is no longer generated by construction activities such that airborne particles will not affect the quality of finished surfaces.

- 4.8.3 Paint and related materials (thinners, solvents, caulking, empty paint cans, cleaning